

DECLARATION OF COMPLIANCE FOR MATERIALS AND ARTICLES
INTENDED TO COME INTO CONTACT WITH FOOD
PAPER KRAFT PE LAMINATED BOWL RANGE

(Revision 6 : 28/04/2026)

SABERT EUROPE
Rue de l'Industrie, N°4
1400 NIVELLES
Belgique

Hereby declare that the products mentioned below:

PAPDG125	Deli2Go rectangular Cup KR 125ml
PAPDG250	Deli2Go rectangular Cup KR 250ml
PAPDG375	Deli2Go rectangular Cup KR 375ml
PAPDELI125	Deli2Go rectangular Cup KR 125ml
PAPDELI250	Deli2Go rectangular Cup KR 250ml
PAPDELI375	Deli2Go rectangular Cup KR 375ml
PAPDELI500	Deli2Go rectangular Cup KR 500ml
PAP12001PE	Portion cup KR FSC MIX Credit 1oz 40x50p
PAP12002PE	Portion cup KR FSC MIX Credit 2oz 40x50p
PAP12008PE	DESSERT ROUND CUP KRAFT PE 250 ML
PAP12012PE	Round Bowl KR FSC MIX Credit 370ml 6x50p
PAP12016PE	Round Bowl KR FSC MIX Credit 550ml 6x50p
PAP12016LPE	LargeRdBowlKR FSC MIX Credit 600ml 6x50p
PAP12024PE	Round Bowl KR FSC MIX Credit 750ml 6x50p
PAP12024EUPE	Round Bowl KR FSC MIX Credit 750ml 6x50p
PAP12033PE	Round Bowl KR FSC MIX Credit 950 ml6x50p
PAP12036PE	Round Bowl KRAF FSC MIX Credit1000ml6x50
PAP12036EUPE	Round Bowl KRAF FSC MIX Credit1000ml6x50
PAP12043PE	Round Bowl KR FSC MIX Credit 1300ml6x50p
PAP12043EUPE	Round Bowl KR FSC MIX Credit 1300ml6x50p
PAP14012PE	Sq Bowl400 KRPE FSC MIX Credit 13cm6x50p
PAP14016NPE	Sq Bowl580 KRPE FSC MIX Credit 13cm6x50p
PAP14024PE	Sq Bowl900 KRPE FSC MIX Credit 17cm6x50p
PAP14032PE	SqBowl1200 KRPE FSC MIX Credit 17cm6x50p
PAP15KSG375	Tray SG KR FSC Mix Credit 375ml 1x400p
PAP15KSG500	Tray SG KR FSC Mix Credit 500ml 1x400p
PAP15KSG750	Tray SG KR FSC Mix Credit 750ml 1x300p
PAP15KSG1000	Tray SG KR FSC Mix Credit 1000ml 1x300p
PAPCOM14012PE30C6	ComSqBowl400 KRPE FSC MIX Credit 6x15+15
PAPCOM14024PE30C6	ComSqBowl900 KRPE FSC MIX Credit 6x15+15
PAPCOM14032PE30C6	ComSqBow1,2L KRPE FSC MIX Credit 6x15+15

Which consist in a paper kraft (virgin fibers) coated on the interior side with a PE lamination film (no adhesive)

Comply with the following regulations:

- **1935/2004** : Regulation (EC) of the European parliament and of the council of 27 October 2004 on materials and articles intended to come into contact with food.

In the following condition of use:

- All type of food .
- Any long storage duration at ambient temperature or below (up to 40°C for more than 30min.)
- Temperature of use: from -20°C to 90°C*
- Hot-fill*
- Do not use in microwave or conventional oven.

* "hot-fill" means the filling of any article with a food with a temperature not exceeding 100 °C at the moment of filling, after which the food cools down to 50 °C or below within 60 minutes, or to 30 °C or below within 150 minutes.

- Lamination complies with **10/2011/EU** and amendments :
The products we supply comply with the overall migration limit of 60 mg/Kg or 10mg/dm² as laid down in regulation 10/2011/EU.

- **Overall migration**

Simulant	Duration	Temperature (°C)	Résultats (mg/dm ²)
Acide acétique 3% (simulant B)	10 d	40	<10
éthanol 10% (simulant A)	10 d	40	<10
Ethanol 95% (simulant D2)	10 d	40	<10
Isooctane (simulant D2)	2 d	20	<10

Ratio surface / volume 1.12 dm²/100ml for global migrations and 0,6 dm²/100ml for specific migrations.

- **Specific migration**

None of the substances submitted to Specific Migration Limit (SML) have been used.

- **Dual use additive only for PAP15KSG******

N° CAS	Names of substances	Food additive number
471-34-1	Calcium carbonate	E170
7757-38-7	Sodium sulfite	E221
7631-90-5	Sodium bisulfite	E222
7681-57-4	Sodium métabisulfite	E223
64-18-6	Formic acide	E236
141-53-7	Sodium formate	E237
50-00-0	Formaldehyde	E240
7631-99-4	Sodium nitrate	E251
127-08-2	Potassium acetate	E261
77-92-9	Citric acide	E330
7558-79-4	Disodium phosphate	E339
124-04-9	Adipic acid	E355
11138-66-2	Xanthan gum	E415
56-81-5	Glycerol	E422

9004-32-4	Sodium carboxymethylcellulose	E466
1338-39-2	Sorbitan monolaurate	E493
7786-30-3	Magnesium chloride	E511
7664-93-3	Sulfuric acide	E513
7757-82-6	Sodium sulfate	E514
10043-01-3	Aluminium sulfate	E520
1310-73-2	Sodium hydroxyde	E524
112926-00-8	Silicon dioxide	E551
57-11-4	Stearic acid	E570
52906-93-1	Starch sodium octenyl succinate	E1450
57-55-6	Propane-1,2-diol	E1520
25322-68-3	Polythylene glycol	E1521
111-30-8	Glutaraldehyde	FL.no 05-149

- **Dual use additive** only for ink in PAP12024EUPE/ PAP12036EUPE/ PAP12043EUPE

N° CAS	Names of substances	Food additive number
1592-23-0	Calcium Stearate	E470a
128-37-0	Butylated hydroxytoluene	E321

- Paper board complies with **German BfR recommendation XXXVI**

- Heavy metals

Chrome VI	<0.25 mg/kg
Mercure	<0.3 mg/kg
Nickel	< 2,0 mg/dm ²
Chrome	< 2,0 mg/dm ²
Plomb	< 0,50 mg/dm ²
Cadmium	< 0,10 mg/dm ²
Aluminium	< 1.0 mg/l

- **DGCCRF** sheet on “organic materials based on vegetal fibers intended to come into contact with food” fiche
- **Phthalates** are not used in the manufacturing process.
- **Commission Regulation (EU) 2024/3190** of 19 December 2024 on the use of bisphenol A (BPA) and other bisphenols and bisphenol derivatives with harmonised classification for specific hazardous properties in certain materials and articles intended to come into contact with food, amending Regulation (EU) No 10/2011 and repealing Regulation (EU) 2018/213.
Recycled FCMs are not within the scope of Regulation (EU) 2024/3190.” (See EC Guidelines Response to Q2).
- **Regulation (EU) 2025/40** of the European Parliament and of the Council of 19 December 2024 on packaging and packaging waste, amending Regulation (EU) 2019/1020 and Directive (EU) 2019/904, and repealing Directive 94/62/EC with regard to:
 - Heavy metal content <100 ppm
 - Absence of identified hazardous substances
 - Absence of PFAS
 - Recyclable

This declaration is supported by comprehensive technical documentation prepared in response to Article 39 and Annex VIII of the PPWR.

- **2023/2006/CE** : commission regulation from 22/12/2006 on good manufacturing practice for material and articles intended to come into contact with food.

Shelf life: 2 years under ideal storage condition: dry, ambient temperature (8°C up to 25°C), in original packaging, not exposed to light.

According to the European legislation in force, this is the responsibility of the end user to verify the technical suitability of the product for his specific intended use.

This letter replaces all previous versions.
Valid two years.

This declaration is done for **Aktum A/S**
Nivelles, 29/05/2026

