



CINTAS
ADHESIVAS
UBIS, S.A.

TECHNICAL SPECIFICATION

PRODUCT: PVC 243 CLEAR

Revisión: 1
Fecha: 09/05/2008
Hoja: 1 de 1

F-0801/06

DESCRIPTION / APPLICATION:

Carton sealing tape, will best suit low temperature applications. Also printable.

Composition

Backing	Unplasticized embossed PVC, clear
Adhesive	Natural rubber and hydrocarbon resin. Clear colour

Characteristics	UNIT.	AVER.	VAR.	
Film Thickness	µm	30	±3	AFERA 4006
Total Thickness	µm	52,5	±4,5	AFERA 4006
Peel Adhesion	N/cm	1,6	±0,5	AFERA 5001
Tensile strenght	N/cm	47	±12	AFERA 5004
Elongation at break	%	75	±30	AFERA 5004

STORAGE: Tape performance is guaranteed within the first 12 months. Keep it in the original box and in a dry atmosphere (between 15°C and 25°C). Batch number (12 digits) showed in the label to be mentioned for tracking origin in case.

SECURITY: Product does not contain any damaging or unhealthy component. Security Data sheets are available based on directive 91/155/EC.
All our tapes do comply with the European 2004/12/CE Packaging directive.