



This document is a **Declaration of Compliance** for the product named below, within the meaning of Article 16(1) of Regulation (EC) 1935/2004 on materials and articles intended to come into contact with food.

DECLARATION OF COMPLIANCE																										
<b>Business Operator:</b>	Colpac Ltd. Enterprise Way, Maulden Rd, Flitwick, Beds, MK45 5BW																									
<b>Product:</b>	Compartment Box																									
<b>Product Type:</b>	Natural Kraft with PE Coating																									
<b>Product Code:</b>	04CTB02K 04CTB03K																									
Declaration of Compliance with																										
<p>We state that the above product complies with:</p> <ul style="list-style-type: none"> <li>Regulation (EC) No. 1935/2004 on materials and articles to come into contact with food (and amendments to date)</li> <li>Commission Regulation (EU) No. 10/2011 on plastic materials intended to come into contact with food</li> <li>Packaging and Packaging Waste Directive 94/62/ EC</li> <li>The requirements of Regulation 2023/2006/EC (GMP)</li> </ul> <p>Colpac is accredited under the BRC Global standard for Packaging Materials and is also ISO 9001 accredited.</p> <p>Based on the information given in our Supplier's Declarations of Compliance all additives and monomers present in their materials are listed in the positive lists of Regulation No. 10/2011 and amendments.</p>																										
Specific Migration Limits (SML)																										
According to our current state of knowledge the PE contains no monomer or additive subject to specific migration limit according to Regulation EU No 10/2011 and its amendments.																										
Overall Migration Limits (OML's)																										
On the basis of the declaration of our supplier, the overall migration tests have been performed on representative samples according to EN 1186-2, 3, 8, 9 and 14 with the following results. The overall migration limit 10mg/dm <sup>2</sup> stipulated in the Commission Regulation (EU) 10/2011 is not exceeded.																										
<b>Paperboard with PE Coating</b>																										
<table border="1"> <thead> <tr> <th>Simulant</th> <th>Contact Time</th> <th>Temperature</th> <th>Max Permissible Limit</th> <th>Result (mg/dm<sup>2</sup>)</th> </tr> </thead> <tbody> <tr> <td>Acetic acid 3%</td> <td>10 days</td> <td>40°C</td> <td>10mg/dm<sup>2</sup></td> <td>&lt;3</td> </tr> <tr> <td>Ethanol 10%</td> <td>10 days</td> <td>40°C</td> <td>10mg/dm<sup>2</sup></td> <td>&lt;3</td> </tr> <tr> <td>Ethanol 95%</td> <td>10 days</td> <td>40°C</td> <td>10mg/dm<sup>2</sup></td> <td>&lt;3</td> </tr> <tr> <td>Isooctane</td> <td>2 days</td> <td>20°C</td> <td>10mg/dm<sup>2</sup></td> <td>3.4</td> </tr> </tbody> </table>	Simulant	Contact Time	Temperature	Max Permissible Limit	Result (mg/dm <sup>2</sup> )	Acetic acid 3%	10 days	40°C	10mg/dm <sup>2</sup>	<3	Ethanol 10%	10 days	40°C	10mg/dm <sup>2</sup>	<3	Ethanol 95%	10 days	40°C	10mg/dm <sup>2</sup>	<3	Isooctane	2 days	20°C	10mg/dm <sup>2</sup>	3.4	
Simulant	Contact Time	Temperature	Max Permissible Limit	Result (mg/dm <sup>2</sup> )																						
Acetic acid 3%	10 days	40°C	10mg/dm <sup>2</sup>	<3																						
Ethanol 10%	10 days	40°C	10mg/dm <sup>2</sup>	<3																						
Ethanol 95%	10 days	40°C	10mg/dm <sup>2</sup>	<3																						
Isooctane	2 days	20°C	10mg/dm <sup>2</sup>	3.4																						
Dual use Additives																										
The used substances do not contain any additives that are authorised as food additives.																										

## Use of the Food Contact Material

The coated paperboard is intended for packaging dry, aqueous, acidic and fatty foodstuffs.

(Y) Indicates the material will withstand the process/temperature

(N) Indicates the material will not withstand the process / temperature

Blast Frozen	Freezer	Fridge chilled	Room temp	Heated Display	Microwave	Oven
N	N	Y	Y	N	N	N

Suitable for long term storage at room temperature or below.


Product is also suitable for contact with food under the following conditions;

- Hot fill/hot hold - Heating up to 70C for up to 2 hours or up to 100C for up to 15 minutes.

iii) ratio of food contact surface area to volume used;

- 100ml/dm<sup>2</sup>

The food contact surfaces fall within the overall migration limit of 10mg/dm<sup>2</sup> as set out in 10/2011

<b>Signed on behalf of Colpac:</b>		Date: 19/11/20
	Frances Dickman Position; Compliance Manager	

### **Disclaimer**

This Declaration of Compliance describes the status of the product(s) and its suitability for intended use. The user of this product(s) is responsible for ensuring that the finished food packaging complies with applicable migration limits in the food itself under actual conditions of use and for verifying possible interactions of the product(s) or its components with the foodstuffs (e.g. modification of odour, taste, consistency, migration etc.) prior to use. This certificate is reviewed every two years or when changes to the product or the relevant Regulations occur.